

Colour Standard / High Resolution Vari-Focal Dome Camera



Features

- 1/3" SONY Super HAD CCD Sensor
- 420 / 520 TV Lines
- 3.7-12mm Vari-Focal Auto-Iris lens
- High Quality ABS and PC Plastic
- 12VDC
- Compact Size

Description

INS-D420VR & D520VR are high performance dome camera with vari-focal auto-iris lens specially designed for low profile indoor surveillance.

The casing is made of high quality ABS and PC plastic to ensure light weight, tough, long lasting and can remain maintenance free for many years.

Various high quality modules are used to ensure customer satisfaction for each installation.

Super Wide Dynamic Model

- INS-D500WDR : 1/3" Pixim Chip, 500 TV Lines



Specification

ITEM	INS-D420VR	INS-D520VR
Signal System	PAL / NTSC	
Image Sensor	1/3" SONY Super HAD CCD Sensor	
Effective Pixel	500H x 582V	752H x 582V
Resolution	420 TV lines	520TV lines
Shutter Speed	PAL 1/50~1/10,000s / NTSC 1/60~1/10,000s	
Video Output	VBS 1.0Vp-p(75Ω Load)	
Sync. System	Internal	
Scanning System	2:1 Interlaced	
S/N Ratio	More than 48dB	
Min. Illumination	0.1 Lux	
Power Supply	DC 12V	
Power Consumption	6-18DCV, 150mA Max.	
Operating Temp.	0℃ ~ +50℃	
Lens	3.7-12mm Vari-Focal Auto-Iris lens	
Optional	2.6-6mm / 9-22mm Vari-Focal Auto-Iris lens	
Dimension	Φ140mm x 90 mm (H)	
Weight	300g	

Specifications are subject to change without any prior notice.