

Colour Standard Fire Sprinkler Camera



Description

INS-S420-FS is high performance fire sprinkler camera specially designed for low profile indoor surveillance.

The casing is made of high quality ABS and PC plastic to ensure light weight, tough, long lasting and can remain maintenance free for many years.

Various high quality modules are used to ensure customer satisfaction for each installation.

Features

- 1/4" SONY Super HAD CCD Sensor
- 420 TV Lines
- 4.3mm Pin Hole lens
- Automatic Electronics Shutter
- AWB, AGC and BLC
- 12DCV

Specification

ITEM	INS-S420-FS
Signal System	PAL / NTSC
Image Sensor	1/4" SONY Super HAD CCD Sensor
Effective Pixel	500H x 582V
Resolution	420 TV lines
Shutter Speed	PAL 1/50~1/10,000s / NTSC 1/60~1/10,000s
Video Output	VBS 1.0Vp-p(75Ω Load)
Sync. System	Internal
Scanning System	2:1 Interlaced
S/N Ratio	More than 48dB
Min. Illumination	0.5 Lux
Power Supply	DC 12V
Power Consumption	110mA
Operating Temp.	0°C ~ +50°C
Lens	4.3mm pin hole lens
Optional	N/A
Dimension	38mm (W) 130 mm (H) x 36 mm (L)
Weight	90g

Specifications and design are subject to change without any prior notice.